



HELL





Helix, where identity begins.

Combining high definition print quality with an intelligent interface and in-line visual security, Helix is the new foundation of trusted identity.



Helix introduces Magicard's latest visual security breakthrough.

An evolution of the famous HoloKote watermark,
Helix utilises a special secure panel to print a security
feature or logo to the card at the point of printing
(Patent Pending). Designed to work with the retransfer
process, HoloKote exploits the wavelengths and lens
effect of the retransfer film to fluoresce under UV
lighting conditions.

Available with 10 watermarks as standard, any of these watermarks can be replaced with your own customised design or company logo through an easyto-use, but securely encrypted, online delivery method.

Innovation. It's what you expect from Magicard.

- Intuitive touch screen interface with print preview and troubleshooting animations.
- Field-upgradable to double-sided printing.
- Superior print quality.
- 1000 capacity ribbons and 200 capacity hoppers.
- Easy load film cassettes to eliminate contamination.
- Backed with Magicard's industry-leading 3 year
 UltraCoverPlus warranty with lifetime warranty on the printhead.







Specifications

Resolution	300 dpi	Extendibility	Internal 4 port USB HUB (1.1). (1x WiFi option, 1x encoder		
Color depth	256 level (8Bit)		option, 1x Micro SD option, 1x unassigned).		
Printing speed	125 card/hr single-sided YMCK (<30 secs)	Memory size	128MB		
	200 card/hr single-sided monochrome	Laminator	Laminator in-line (double-sided) option		
Feeder capacity	200 cards (0.76mm/0.029")		(available 2	016).	
Card exit capacity	200 cards (0.76mm/0.029")	Card encoding options	Magnetic stripe (ISO 7811, JIS2, custom formats), Contact (ISO 7816 & EMV), Contactless (MIFARE, DESFire, ProX,		
Card thickness	0.76mm to 1.25mm (30 mil to 49 mil)		*	& EMV), Contactiess (MIFAR , TagIT, Legic, UHF.	E, DESFIRE, PROX,
Card size	CR80	Printer security	Standard: Kensington lock.		
Card material	PVC, PET, PC, PVH, ABS,		Option: Us	er log-on, secure film cassett	es, secure blank
Display	TFT LCD panel, Size: 4.3 inch, Resolution: 480x272,		media feed	er, secure card reject hopper	, ribbon erase facili
	Color depth: 16.7 million colors, Resistive touchscreen.	Security watermark	Standard HoloKote with UV effect (10 standard designs) – for use with secure dye film only.		
Dimensions	H 420mm (16.5") x W 455mm (17.9") x D 330mm (13")				
Estimated weight	14.4Kg/31.7lb	Customised watermark	Custom HoloKote with UV effect - ordered separately and		
Power source	100-240VAC		for use with secure dye film only.		
Interface	USB 2.0, 10 BASE-T/100 BASE-T Ethernet.				
	802.11 b/g/n WiFi (option).	Part numbers			
System requirements	Windows XP, Vista, 7, 8.1, 10 (32 and 64bit) Windows server	Single-sided		Double-sided	
	2003 R2 SP2, 2008, 2012, 2016, GNU/Linux and Mac OS X	Helix Uno	3663-001	Helix Duo	3663-0021
Printer warranty	3 years UCP USA, EU, Australia and selected other territories	Helix Uno Mag	3663-002	Helix Duo Mag	3663-0022
	otherwise 3 years limited.	Helix Uno Smart	3663-003	Helix Duo Smart	3663-0023
Printhead warranty	Lifetime	Helix Uno Smart Mag	3663-004	Helix Duo Smart Mag	3663-0024

Consumables

Helix film sets	Print capacity	Product code
Colour dye film and retransfer film set (1 YMCK and 1 RT film)	1000 images	SET-HX1000
Colour dye film with secure HoloKote panel and retransfer film set (4 YMCKS and 3 RT films)	3000 images	SET-HX3000S
Black monochrome dye film and retransfer film set (1 black and 3 RT films)	3000 images	SET-HX3000K
Helix dye films	Print capacity	Product code
Colour dye film (YMCK)	1000 images	HX1000YMCK
Colour dye film with secure HoloKote panel (YMCKS)	750 images	HX750YMCKS
Double-sided dye film, prints colour on one side and black on reverse (YMCKK)	750 images	HX750YMCKK
Black monochrome dye film (K)	3000 images	HX3000K-BLAC
Colour dye film with UV panel (YMCKUv)	750 images	HX750YMCKU
Helix retransfer films	Print capacity	Product code
Retransfer film	1000 images	HX1000RT
Extra durable retransfer film	1000 images	HX1000RTD



Global contacts



Headquarters and manufacturing centre

Hampshire Road, Weymouth, Dorset DT4 9XD, United Kingdom

Tel: +44 (0) 1305 767 100 Fax: +44 (0) 1305 777 904 Email: info@ultralD.com



China sales and support centre

Room 902 Zhonghuang Tower, No.1007 Second Zhongshan Road (S) Xuhui District Shanghai 2000030, PRC.

Tel: +86 21 6457 3509 Fax: +86 21 6457 3509 Email: china@ultralD.com



All other trademarks, brand names, or product names belong to their respective holders.

The information contained in this document reflects the current state of design and we reserve the right to change the specification without notice or obligation.



Americas sales and support center

6724 - 185th Avenue NE, Suite A, Redmond, WA 98052, USA

Toll free: 877 236 0933 Tel: +1 (425) 556 9708 Fax: +1 (425) 556 3962 Email: americas@ultraID.com



Middle East sales and support centre

4WB (West Wing) Office - 652, Dubai Airport Free Zone, PO Box: 54974, Dubai, United Arab Emirates

Tel: +971 4 260 2930 Fax: +971 4 260 2931

Email: uae@ultraID.com